



Wuxi Hiwell Diatek Instruments Co., Ltd

• Main Features

- ◆Large LCD display, menu designed for convenient use
- Whole plate washing or single strip washing
- ◆12-way and 8-way manifold included
- Low residual volume by two pipettes
- ◆Complete bottom washing
- Shaking and dipping function
- Automatic monitoring of vacuum and pressure ,automatic rinse cycle
- Flat, V-bottom or U-bottom plate and strips washing
- ◆ Large memory to store up to 120 user programmed wash protocols
- Emergency stop available and liquid warning





• Technical Specification

Input	8 key membrane keyboard
Display	High brightness LCD display screen
Manifold	8 pins and 12 pins
Wash mode	Strip mode and plate mode
Wash strips	1~12 adjustable
Applicable well	Flat, V-bottom or U-bottom
Wash time	0~99 times adjustable
Soak time	0~3600s adjustable
Shake time	0~600s adjustable
Residual volume	≤1µL/well
Liquid volume	50~3000ul/well
Siptime	0.1~9.9s
Storage capacity	More than 120 user defined wash board procedures
Power supply	100~240V,50~60Hz
Dimensions	448(L)×382(W)×163(H)mm
Net weight	8kg
Operating environment	Temperature 5°C ~40°C ,Max humidity 80%



Wuxi Hiwell Diatek Instruments Co.,Ltd